C64GS TECH DATA

NOVEMBER, 1990

PN-400401-01

SPECIFICATIONS

FEATURES

MICROPROCESSOR: 6510A, 1MHz clock — Compatible with 6502

MEMORY: 64K

ROM: 20K ROM standard includes operating system

DISPLAY: 40 columns x 25 lines of text

COLOURS: 16 background, border and characters

DISPLAY MODE: Text characters — High resolution graphics

RESOLUTION: 320 x 200 pixels

SPRITES: 8 independent sprites, each consists of 24 x 21 pixels and

up to 4 colours, each independently expandable horizontally

and vertically

SOUND: 6581 Sound Interface Device includes 3 independent tone

generators

PORTS: ROM cartridge port, 2 joystick ports

SYSTEM INTERFACES

SIDE PANEL CONNECTIONS

POWER CONNECTOR: Uses standard C64 power supply POWER SWITCH: Supplies power to the system

JOYSTICK PORTS: Two standard DB9 connectors

TOP CONNECTIONS

CARTRIDGE SLOT: The rectangular slot accepts program or game cartridges

REAR CONNECTIONS

MODULATOR SWITCH: A switch is provided on the modulator to change the audio

carrier between 6MHz (UK) and 5.5MHz (continental

Europe).


RF OUTPUT: Supplies both the picture and sound to a PAL television set.


AUDIO/VIDEO OUTPUT: This is a C64 style 8 pin DlN connector for Luma Chroma


Audio connections to a PAL monitor

POWER REQUIREMENTS

240V, 50Hz







PART NAME

TOP CASE ASSY


BOTTOM CASE ASSY NTSC BOTTOM CASE ASSY PAL SCREW, SELF TAP #5 TORX 3/8 * OTY = 5


REF. NO.

PART NO.


363495-01

313491-01 313491-02 390177-02






C64 GAME SYSTEM ASSEMBLY DIAGRAMS



Commodore Internat PCB Coi PCB Assembly #250


IC COMPON	ENTS		RESISTORS	5% @ 1/4 WATT, CARBON FILM, UNLESS OTH	erwise specified
318012-01 906108-01 318027-01 318013-01	8500 6526 8565 8580 2332 ROM CHAR	U6 U1,U2 U7 U9 U5 U5 U18,U21	251068-65 251068-69 251068-76 251068-101 251068-126	390 OHM 560 OHM 1K 10K	R5 R16 R3,R12 R9,R17 R14 R101
901522-06 901521-03 901521-30	7406 74L508 74LS14	U22 U3 U23	251068-B2 CAPACITOR	S	R19 R100
251527-08 251527-09 901453-07	B701L6	U20 SUB FOR 251527-08 U19 (USE W/U8 & REV A PCB)	251069-12	CER RAD 470 PF 50V CER RAD 2000 PF 50V CER RAD 0.1 UF 25V	C2-4,6,76,90 C80,C81 C1,7,28-30,34,35,37,39, 40,47,48,55,61,69,79,84
		U10,U11 SUB FOR 390083-02 U19 U22 SUB FOR IC 7406	251079-06 900100-11	CER RAD 22000 PF 50V ELEC 2.2 PF 50V ELEC RAD 4.7 PF 25V ELEC RAD 10 PF 25V	C70,C71 C44 C59 C77
390083-05 390889-01	64K X 4 BIT DRAM 64K K 4 BIT DRAM 128K ROM (GAME) U.S. PAL MEMORY CONTROLLER	U10,U11 SUBSTITUTE U10, U11 SUBSTITUTE U4 U8 SUB USE W/REV A	900100-40 900100-03 900101-52	ELEC RAD 100 PF 16V ELEC RAD 220 PF 25V ELEC RAD 1000 PF 16V ELEC RAD 47 PF 16V	C58 C65 C63 C36
	MEMORY CONTROLLER	PCB U8	900100-1B 390101-07	ELEC RAD 220 PF 16V ELEC RAD 470 PF 35V ELEC RAD 22000 PF 25V	C43 C66 C70,C71 SUB FOR
902441-22 902412-07	TK 6PIN 5EL 3.3K 9PIN BEL 3.3K BPIN 7EL	RP6 RP4 RP3,RP5	251029-02	TRIMMER 7.7-40 PF CER RAD 0.01 UF	251304-71 CT-1 C56




ional Spare Parts List

mponents 469-09, -10, REV. B

CONNECTOR	as		MISCELLAN	EOUS (Continued)	
251116-01 252168-01 251067-01 90332-03 251251-01 MISCELLAN 903025-08 252214-01 325563-01 252341-01 251878-02 251878-01 251468-01 200018-13 901151-17 900750-01 251819-01 906103-04 906103-05	7 PIN - POWER B PIN - AUDIO/VIOEO 9 PIN MINI O - CONTROL PORTS HEADER ASSY 3 PIN 44 PIN CARD EDGE - EXPANSION EOUS FERRITE BEAO LONG FERRITE BEAO 2 TURN FERRITE BEAD RF CHOKE COIL LINE FILTER B TERMINAL LINE FILTER B TERMINAL CRYSTAL 17.73447 MHZ JUMPER WIRE COIL INDUCTOR 2.2 DIODE IN4001 DIODE IN4001	CN7 CN5 CNB, CN9 CN10 CN6 FB7-FB10 FB1 FB2,3.4 (FB4 S/B COVEREO W/ ASHRINK TUBE) L3,4 L1 L1 SUB FOR 251B78-02 Y1 CL 1BPF USE ON Y1 L2 CR3.4 CR5.9,11-21 CR5.9,11-21 CR6.9,11-21 SUB FOR 251B19-16 CR6 SUB FOR 906103-04 CR7 FOR 8580 (HMOS SIO)	252026-01 251026-02 251026-03 251842-01 390257-03 902694-01 9251526-01 251526-01 252338-01 252405-03 904150-06 904150-06 903556-18 906102-02 904500-01 904500-01 904500-01 904500-01 904500-01 904500-01 904500-01	DIODE BRIDGE RECT S2VB 10 DIODE BRIDGE RECT DBA20B OIODE BRIDGE RECT DBA20C EMI FILTER 270PF EMI FILTER 270PF TRANSISTOR 2SC1B15 TRANSISTOR 2SC245B TRANSISTOR 2SC245B TRANSISTOR PROPORTIVE MODULATOR - PAL SOCKET 16 PIN (USE DN U20) SOCKET 18 PIN (USE DN U4,U9) SOCKET 18 PIN (USE ON U4,U9) SOCKET 40 PIN (USE ON U7) FUSE. NORMAL BLO 250V 1.5A FUSE, CLIP (USE ON F1) FUSE CLIP SWITCH, ROCKER DPOT CARTRIDGE GUIOE · CONSOLE	CR2 SUB FOR 251026-01 SUB FOR 251026-01 EMI1-9 OST310-55Y55271M EMI1-9 SUB OSS310-55Y5S271M O2.03 02.03 SUB 02.03 SUB 05 M1
252337-61	DIODE ZENER HZ11A1	Vz = 9.48-9.90 AT 5mA SUB FDR 252313-63			



ì




CARTRIDGE EXPANSION SLOT CN6

22 21 39 19 18 17 14 15 14 13 12 11 18 9 9 7 9 9 4 3 2 1


PIN	TYPE	PIN	TYPE
ı	GND	A	GND
2	+ 5V	В	ROMH
3	+5V	С	RESET
4	ĪRQ	D	NMI
5	R/W	E	S 02
6	Dot Clock	F	A15
7	1/D 1	H	A14
8	GAME	J	A13
9	EXROM	K	Al2
10	1/0 2	L	A11
11	ROML	M	A10
12	BA I	N	A9
13	DMA	P	A8
14	70	R	A7
15	D6	S	A6
16	D5	T	A5
17	D4	U	A4
18	D3	V	A3
19	D2	w	A2
20	ן סו	l x l	AL
21	00	Y	A0 -
22	GND	Z	GND

JOYSTICK CN8, CN9




PIN	PORT 1 TYPE	PORT 2 TYPE
	JOYA0	JDYB0
2	JDYA:	JDYB!
3	JDYA2	JOYB2
4	JOYA3	JOYB3
5	POT AY	POT BY
6	BUTTON A/LP	BUTTON B
7	+ 5V (Max 50MA)	+ 5V
8	GND	GND
9	POT AX	POT BX

AUDIO/VIDEO CN5



. <u> </u>					
Į	PIN	TYPE	PIN	TYPE	
ĺ	1	LUM	5	AUD/IN	_
	2	GND	6	COLDR	
	3	AUD/OUT	7	NC	
	4	COMPOSITE	8	+5	

POWER CN7



PIN	TYPE	PIN	TYPE
1	NC	5	+5 VDC
2	GND	1 6	9VAC
3	NC	7	9 VAC
4	NC	17	

TROUBLESHOOTING GUIDE C64 GAMES SYSTEM (C64 E PCB)

SYMPTOM

Abnormal colors appear in text

Wrong characters are displayed

System does not reset

White band scrolls down the screen (60/50 Hz Hum)

Wavy screen after system warms up

Black band scrolls through screen when system warms up

Blank screen on power up

System powers up with all characters displayed as blocks

Intermittent display

Joystick does not operate correctly

Wrong frequency

No text is displayed

Graphic characters displayed instead of text displayed

No Sound

POSSIBLE SOLUTION

Check U19 (2114 RAM); U21 (4066); U7 (VIC)

Check RAM (UI0,UII)

Check U20 (556 IC)

Check External Power Supply; VR2 (5V regulator)

Check External Power Supply — U20, U7

Check External Power Supply; CR2, C65, C66

Check External Power Supply; U4 (Kernal/Basic ROM); U8 (MMU); U6 (MPU); U7 (VIC); U22,

U23; U10, U11 (RAM); C22

Check U8 (MMU); U7 (VIC)

Check Connectors — C63, C66

Check Ul (CIA); UI8 (4066); EMI 1-9

Check C70, C41

Check U4, U5 (ROMS); U2 (CIA); U7 (VIC)

Check U7 (VIC); U2 (CIA); U8 (MMU)

Check U19 (SID); FI (Blown fuse)